

Cheque Personalization Encoder / Printer



BP 65

Tape Dispenser

BP 65S



General Specification:

New BP 65 Cheque and Document printer encode and print Cheques and Giro.
BP 65 is a perfect printer for Banks, Financial Institutions, Security Management, wherever high quality and security printing is required.
For the purpose of security and to prevent Fraud, only IMPACT printing stations are used in combination with ribbons with different security ink. Security ink may be used in one or all the 8 impact printing stations.
BP 65 takes maximum advantages of the available technology providing a powerful production environment for pre-encoding and personalisation of cheques or value documents.

ADVANTAGES:

- Easy to maintain and service
- Windows driver
- Easy data base design
- Maximum Security with passwords
- Unlimited queue list, with VIP transfer
- Flash Programmable
- Audit Trail (options)
- Connection of 2 units in the software (options)
- Up to 20 number of document format's (options)

BP65 / BP65S

Specifications			
Model	Low cost type	BP 65: MICR & Personalisation encoder with 7 Dot matrix printer stations.	
	Standard type	BP 65S: Same as BP65 + Stapler function and Label holder.	
Document Feeder	Type	Auto Feeder	
	Capacity	BP 65	500 documents
		BP 65S	500 documents
MICR Encoder	Font	E13B or CMC7 (factory option)	
	Encoding fields	All fields (Max 65 columns)	
	MICR ribbon type	Cassette one-time ribbon (85,000 characters/cassette)	
Impact Dot Matrix Printer (9 pin In line) (9 pin staggered)	Number of printing character	Total 120 characters/head	
	Printing character font	Numeric & Alphanumeric, 5 different fonts included.	
	9 pin in line 9 pin staggered	Generally used Used for printing OCRB font.	
Output Stacker	Capacity	BP 65	500 documents
		BP 65S	500 documents
Stapler (5000 staples)	BP 65	No	
	BP65S	Yes	
Label cassette	BP 65	No	
	BP65S	Yes	
Document Specification	Length	140 - 275 mm	
	Height	65 - 115 mm	
	Thickness	80 -120 gr/sq.m	
Processing speed		30 documents/min (encoding 30 MICR characters + 7 personalisation lines.)	
Dimension	BP65	93 cm x 45cm x 37,5cm	
	BP65S	93 cm x 45cm x 37,5cm	
Weight	BP65	36 kg	
	BP65ES	37.5kg	
Power Supply		110-220V(10%), 50/60Hz	
Communication Interface		RS232C (9600 bps)	

Arctic Heating AS
Smidsrødveien 95, Box 164 Teie
N-3106 Tønsberg - NORWAY

Telephone +47 33 30 42 20
Fax +47 33 32 29 02
Electronic mail: arctic@heating.no
Homepage: www.arctic-heating.com